



# WANLI

**TBR**



**2021**

**CATALOGO**



**SAH01/**(47)



**SAH02/**(48)



**SAH03/**(47)



**SFR01/**(48)



**SFR06/**(49)



**HIGHWAY SERIES**



HIGHWAY SERIES

**STR05/** (49)



**STR658(+)**/(50)



**SAR566/** (50)



**SAU01/**(51)



**SAU02/**(51)





**LONG HAUL**

**SDR01/***(52)*



**SDR800/***(52)*



**SDR03/** *(53)*



**MIXED**

**SAM02/** *(53)*



**SAM521(+)***(54)*





# WANLI

MIXED

**SDM868/(54)**



**SDM901(+)/(55)**



**SDM963(+)/(56)**



**SAP08(+)/(56)**





**ESTOVAN**

www.estovan.com

**WANLI**



# SAH01

Highway Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
255/70R22,5	16PR	13,1	140/137	K	7,50	2500/2300	830
215/75R17,5	16PR	12,1	135/133	J	6,00	2180/2060	865
235/75R17,5	18RP	13,6	143/141	J	6,75	2725/2575	865
205/75R17,5	14RP	12,1	124/122	M	6,00	1600/1500	750



Highway Series

# SAH02

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
215/75R17,5	16PR	12,1	135/133	J	6,00	2180/2060	865
235/75R17,5	18PR	12,1	143/141	J	6,75	2725/2575	865
205/75R17,5	14/G	12,1	124/122	M	6,00	1600/1600	750





**ESTOVAN**

www.estovan.com

**WANLI**



# SAH03

Highway Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
9,5R17,5	18PR	13,6	143/141	J	6,75	2725/2575	875
275/70R22,55	16/H	15,1	148/145	M	8,25	3150/2900	900



Highway Series

# SFR01

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
275/80R22.5	16PR	14,6	149/146	M	8,25	3000/2725	830
275/80R22.5	18PR	14,6	149/146	M	8,50	3250/3000	900





**ESTOVAN**

www.estovan.com

**WANLI**



## SFR-06 Highway Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
255/70R17,5	16PR	13,1	140/137	K	7.50	2500/2300	830
255/70R17,5	18PR	13,1	152/148	G	7.50	3550/3150	930



Highway Series

## STR05

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
315/80R22.5	20PR	16,9	156/150	L	9,00	4000/3350	850
12R22.5	18PR	16,9	152/149	L	9,00	3550/3250	930







**ESTOVAN**

www.estovan.com



## STR658(+)

Highway Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
295/80R22.5	18PR	16,9	150/147	L	9,00	3350/3075	830



Highway Series

## SAR566

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
12R2,25	18PR	15,6	152/149	L	9,00	3350/3250	930





**ESTOVAN**

www.estovan.com

**WANLI**



# SAU01

Highway Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
275/70R22,5	18PR	19	144/141(152/148)	J(E)	8,25	2800/2575	830



Highway Series

# SAU02

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
215/75R17.5	18PR	15.1	135/133	J	6,00	2180/2060	850





**ESTOVAN**

www.estovan.com

**WANLI**



**SDR01**

LONG-HAUL

Tire Size	PR/LR	Tread Depth		Load Index S/D	Speed Symbol	Std. RIM	Section Width		Overall Diamete		Load Capacity			Std.cold infl. Press	
		mm	32nds				mm	inch	mm	inch	kg(S/D)	lbs(S)	LBS(D)	KPA	PSI
215/75R17,5	16/H	13,6	17	135/133	J	6,00	212	8,3	767	30,2	2180/2060	4805	4540	865	125
235/75R17,5	18/J	13,6	17	143/141	J	6,75	233	9,2	797	31,4	2725/2575	6005	5675	865	125
315/80R22,5	20/L	20,4	26	156/150	L	9,00	312	12,3	1082	42,6	4000/3350	8820	7390	850	123
265/70R19,5	14/G	15,1	19	140/138	M	7,50	262	10,3	867	34,1	2300/2120	5070	4675	760	119



LONG-HAUL

**SDR800**

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
295/80R22.5	18PR	20,4	152/149	L	9,00	3350/3250	900





**ESTOVAN**

www.estovan.com



## SDR03 LONG-HAUL

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
295/80R22,5	16PR	17,4	152/148	M	9,00	3550/3150	850



## Mix Series SAM02

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
7,50R16LT	14PR	14,1	122/118	L	6,00G	1500/1320	770
8,25R16LT	16PR	14,6	128/124	K	6,50H	1800/1600	770





**ESTOVAN**

www.estovan.com



## SAM521(+)

Mix Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
825R16LT	16PR	14,6	128/124	K	6,50H	1800/1600	770
315/80R22.5	20PR	16,9	157/154	K	9,00	4125/3750	900
295/80R22.5	20PR	20,4	154/149	L	9,00	3750/3250	850
7,50R16LT	14PR	14,1	122/118	L	6,00G	1500/1320	770
12R22.5	18PR	15,9	152/149	L	9,00	3550/3250	930



Mix Series

## SDM868

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
9,5R17,5	18PR	13,6	143/141	J	6,75	2725/2575	875





**ESTOVAN**

www.estovan.com

**WANLI**



## SDM901(+)

Mix Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
315/80R22.5	20PR	21,7	157/154	J	9,00	4125/3750	900
12R22.5	18PR	19	152/149	K	9,00	3550/3250	930



Mix Series

## SDM963

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
295/80R22.5	20PR	21,4	154/149	G	9,00	3750/3250	850



**ESTOVAN**[www.estovan.com](http://www.estovan.com)

# SAP08(+)

## Mix Series

Size	PR	Tread Depth	Load Index	Speed Symbol	Std. RIM	Max Load (kg)	Std.cold(KPA)
12R22.5	20PR	23,7	154/151	F	9,00	3750/3450	970

